

Business-Class Video Conferencing for the Small Meeting Room

lifesize

Lifesize® Icon Flex™



It's Your Meeting—You Choose the Application

At Lifesize, we know there's a better way to have an exceptional meeting experience because we've spent over a decade perfecting it. Meet Lifesize Icon Flex—a complete, business-class video and audio conferencing solution ideally suited for small meeting rooms that gives businesses the power of choice. So whether your business is using Microsoft® Lync®, Google Hangouts™, Cisco Jabber®, Skype™, or our favorite, Lifesize® Cloud, all you have to do is bring your laptop to the meeting and connect it to Lifesize Icon Flex for a video collaboration experience like no other.

And what makes Lifesize Icon Flex stand out from the rest is that our elegantly designed Lifesize Phone can also be used as a stand-alone conference phone, giving your company one less device to manage in the meeting room.

Best of all, Lifesize stands by every solution we make with our world-class service and support team.

Your laptop. Your collaboration app. Lifesize Icon Flex. It's that simple.



Your Meeting, Your Way

- Perfectly sized for small meeting rooms
- Designed for use with collaboration applications like Microsoft Lync, Google Hangouts, Cisco Jabber, Skype (or our favorite, Lifesize Cloud)
- Business-class, award-winning hardware provides an exceptional meeting experience
- Backed by our world-class customer service and support team that's always there when you need them

LIFESIZE CAMERA

- Provides superb, lifelike HD 1080p30/720p60 video
- Ultra-quiet pan/tilt with 6x zoom: 3x optical zoom and 2x digital zoom
- Low-dispersion, 8-element glass lens, with anti-glare coating and high clarity, molded aspherical glass
- Proprietary lens iris reduces optical diffraction
- Razor-sharp image quality provided by five-zone autofocus
- Increased durability and optimal heat distribution through machined aluminum body

LIFESIZE PHONE

- Elegantly designed touchscreen conference phone with 360° microphone coverage and powerful loudspeaker for maximum voice pickup and crystal-clear audio
- Can be used as a stand-alone audio conference phone by connecting to your IP-PBX

LIFESIZE REMOTE CONTROL

- Controls camera (pan/tilt/zoom) and audio (mute/volume)

SYSTEM COMPONENTS

Lifesize Icon Flex with embedded PTZ camera
Lifesize Phone or Lifesize Digital MicPod
Lifesize Remote Control
Power supply and cable (2 m)
USB A to USB B cable (5 m)
Ethernet cable (3 m)
Quick reference card

SYSTEM REQUIREMENTS

Windows 7 or higher
Mac OS X 10.8 or higher
USB 2.0 port

DESIGNED FOR USE WITH:

Microsoft Lync
Google Hangouts
Cisco Jabber
Skype
Lifesize Cloud
Windows®
Mac®

TECHNICAL SPECIFICATIONS

HD video resolution with 6x PTZ camera
– Progressive scanning
– 16:9 aspect ratio
– Wide-angle zoom lens with 70-degree field of view
– 245-degree pan, 72-degree tilt
– 3x optical lossless zoom
– 2x digital zoom
– Power LED

VIDEO OUTPUT (1)

1 x USB B (1080p30/720p60) to laptop
Laptop can be connected to HD display separately

FULLY INTEGRATED, HD AUDIO LIFESIZE PHONE

90 Hz up to 22 kHz
32 kHz audio sampling
Pickup range up to 4.57 m (15 ft)
Powered by Lifesize Icon Flex through Lifesize Link cable
Ships with 9 m Lifesize Link cable
Optional 4 m or 15 m cable available

System Speaker
– Powerful rare-earth magnet loudspeaker driver
– Large, acoustically suspended speaker enclosure

System Microphones
– Four low-noise microphones
– 80 dB SNR before noise reduction
– Sample rates: 32 kHz
– Beam-forming algorithm steers the microphones to the location of the talker for greater voice pickup and reduced room noise

Touchscreen Display
– WQVGA capacitive multitouch display
– 4.3 inch (diagonal)

FULLY INTEGRATED, HD AUDIO LIFESIZE DIGITAL MICPOD

90 Hz up to 22 kHz
Sample rates: 32 kHz
Pickup range up to 4.57 m (15 ft)
Powered by Lifesize Icon Flex through Lifesize Link cable
Ships with 4 m Lifesize Link cable
Optional 9 m or 15 m cable available

System Microphones
– Three low-noise microphones
– 80 dB SNR before noise reduction

GENERAL AUDIO FEATURES

Full duplex for natural conversations
Echo cancellation for echo-free calls
Automatic gain control
Automatic noise reduction

AUDIO INPUT (1)

1 x Lifesize Link (Lifesize Phone/Digital MicPod) via USB cable to laptop

AUDIO OUTPUT (1)

1 x Lifesize Link (Lifesize Phone) via USB cable to laptop

USER FEATURES

Heads-up remote control
Intelligent touchscreen interface with Lifesize Phone
Manage camera pan, tilt, zoom, audio mute/unmute, volume up/down
LEDs on phone or micpod for in-call (blue) and mute (red) indication

SECURITY

Kensington Security Slot

POWER

AC voltage 100–240V, 50–60 Hz, 2.31A via external 19VDC power supply

ENVIRONMENTAL DATA

Operating temperature: 0°C (32°F) to 40°C (104°F)
Operating humidity: 15% to 85%, noncondensing
Storage temperature: –20°C (–4°F) to 60°C (140°F)
Storage humidity: 10% to 90%, noncondensing

DIMENSIONS

Width: 216.5 mm (8.52")
Depth: 119.4 mm (4.70")
Height: 125.4 mm (4.94")
Weight: 1.04 kg (2.29 lbs)

MOUNTING OPTIONS

Mounting holes: 2 x M5 screw holes 150 mm (6 in) apart
Mounting screws: 2 x M5 screws (Max insertion depth: 3.8 mm)

REGULATORY NUMBER:

LFZ-033

RUNS ON:



DESIGNED FOR USE WITH:



Performance dependent on collaboration application being used.

HEADQUARTERS

Austin, Texas, USA
+1 512 347 9300
Toll Free US +1 877 543 3749

APAC REGIONAL OFFICE

Singapore
+65 6303 8370



www.lifesize.com
E-mail: info@lifesize.com

EMEA REGIONAL OFFICE

Munich, Germany
+49 89 20 70 76 0
Toll Free Europe +00 8000 999 09 799

lifesize

© 2015 Lifesize, a division of Logitech. All rights reserved. Information contained in this document is subject to change without notice. Lifesize is the registered trademark or trademark of Logitech. All other trademarks are the property of their respective owners.

DS_IconFlex_EN_0115